

PATHMAT™

Product Data Sheet

Issue: 01.PM06 Date: 08.12 Page: 1 of 1

Physical Properties	Standard 0.24lbs/ft ²	
Structure	Oscillated	
Polymer	Elastomeric PE Blend	
Color Options	Light Blue	
UV Stabilized	Yes	
Dimensional Characteristics		
Roll Width	ft	5
Roll Length	ft	32.8
Roll Weight	lbs	12.5
Weight per Square Foot	lbs	0.76
Thickness	in	0.50
Aperture (Diamond Oval)	3:1 ratio	
Technical Characteristics		
Tensile Strength (MD)	(1)	16 kN/m
Yield Point Elongation (MD)	(1)	130%
Residual Thickness at 500 kPa	(2)	22%
Slip Risk PTV Value	(3)	>40 (low slip)

PATHMAT U-Pins

Product	U-Pin	
Material	Rebar Type Galv Wire	
Size	in	6 x 16 x 0.36
Packaging	10 Pack	

Testing Methods:

- (1) ISO 10319
- (2) ASTM D1621
- (3) BS7976: 1-3

As part of its continual improvement process, Fiberweb, Inc. reserves the right to change the properties listed on this data sheet without prior notice.

* indicates a registered trademark of Fiberweb, Inc. or a Fiberweb Group company, many of which are registered in a number of countries around the world.